

Data-Free Neural Architecture Search via Recursive Label Calibration

Zechun Liu^{1,2}, Zhiqiang Shen^{1,2,3*}, Yun Long⁴, Eric Xing^{2,3}, Kwang-Ting Cheng¹, and Chas Leichner⁴

¹ Hong Kong University of Science and Technology, ² Carnegie Mellon University

³ Mohamed bin Zayed University of Artificial Intelligence, ⁴ Google Research
zliubq@connect.ust.hk, zhiqiangshen0214@gmail.com, longy@google.com,
epxing@cs.cmu.edu, timcheng@ust.hk, cleichner@google.com

Abstract. This paper aims to explore the feasibility of neural architecture search (NAS) given only a pre-trained model without using any original training data. This is an important circumstance for privacy protection, bias avoidance, etc., in real-world scenarios. To achieve this, we start by synthesizing usable data through recovering the knowledge from a pre-trained deep neural network. Then we use the synthesized data and their predicted soft labels to guide NAS. We identify that the quality of the synthesized data will substantially affect the NAS results. Particularly, we find NAS requires the synthesized images to possess enough semantics, diversity, and a minimal domain gap from the natural images. To meet these requirements, we propose recursive label calibration to encode more relative semantics in images, as well as regional update strategy to enhance the diversity. Further, we use input and feature-level regularization to mimic the original data distribution in latent space and reduce the domain gap. We instantiate our proposed framework with three popular NAS algorithms: DARTS, ProxylessNAS and SPOS. Surprisingly, our results demonstrate that the architectures discovered by searching with our synthetic data achieve accuracy that is comparable to, or even higher than, architectures discovered by searching from the original ones, for the first time, deriving the conclusion that NAS can be done effectively with no need of access to the original or called natural data if the synthesis method is well designed. Code and models are available at: <https://github.com/liuzechun/Data-Free-NAS>.

1 Introduction

Neural architecture search (NAS) has demonstrated substantial success in automating the design of neural networks [35, 1, 21, 20, 14, 26, 11]. A typical NAS algorithm usually involves three core components: a search space, a search algorithm, and a set of training data. The majority of researches in NAS focuses on search space design [15, 30] or exploring superior search algorithms [4, 27]. While, in

* Corresponding author.

This work is done when Zechun Liu is an intern at Google Research.

this study, we investigate the feasibility of performing neural architecture search without accessing the original training data. We assume that we only have a pre-trained model, and the original dataset is not accessible during the neural architecture search process. This is a common and useful circumstance that is needed to be solved urgently for privacy protection, bias avoidance, etc. We call this *data-free NAS*, a practical task for application scenarios in which privacy or logistical concerns restrict sharing of the original training data but permit sharing of a model trained by such data for NAS. Also, models are usually smaller in size than large-scale datasets, which makes them easier to exchange and store.

Conducting NAS without data is challenging. Traditional NAS relies on the input images to train and rank different architectures. A natural image dataset contains semantic patterns and inter-class relationships, which are helpful in guiding architecture search. For scenarios where the original data is not accessible, we first need to synthesize an image dataset from the model pre-trained on the original data, and use such a synthesized dataset for conducting architecture search. This, however, raises a crucial question: how do we synthesize an image dataset that has the important search-relevant attributes or properties of the original data for effective NAS without using any of the original data?

Currently, data-free NAS is an under-explored task that requires unique understanding of the particular synthesized data. In this work, we empirically identify three attributes that NAS in data-free scenario requires the synthesized images to have: (i) rich semantic information, (ii) sufficient image diversity, and (iii) a minimized domain gap with the original data. Rich semantic information ensures the classification task on the synthesized images is as complex as that of the original training images. High image diversity prevents the NAS algorithms from overfitting to the synthesized data and producing trivial solutions. A minimized domain gap makes certain that architectures found by searching over the synthesized data also can perform well on the original data.

To fulfill these requirements, we propose a novel image synthesis method for promoting the effectiveness of architecture search procedure. As shown in Fig. 1, we synthesize the images using gradient descent with respect to class labels. We observe that conducting NAS on data synthesized from one-hot labels leads to overfitting and the models searched by the NAS algorithms fail to generalize to the original training data. This issue is caused by one-hot labels’ limitation of being unable to capture the full set of semantic relationships between classes in the original training data. For instance, the synthesized images will be confidently classified as a single class (*e.g.*, “coffee mug”) but with no trace of similarity to other relevant classes (*e.g.*, “cup”). To avoid this, we propose *recursive label calibration* for finding semantically-significant soft labels.

As shown in Fig. 1 (a), we use logits derived from the pre-trained model as the class labels during the image synthesis process. Starting from a hard label, *i.e.*, one-hot distribution, we recursively apply this labeling process to successive batches of images to amplify the representation of classes which are semantically related to the original target class while only weakly presented in the initial image synthesis. We show that images synthesized using recursive label calibration are




Fig. 1. The proposed data-free NAS framework consists of two stages: (a) image synthesis using recursive label calibration, and regional update; (b) running an architecture search using the synthesized images. Specifically, the image synthesis stage consists of an **Inner Loop** and an **Outer Loop**. The **Inner Loop** starts with a random noise input, which is then updated with the gradient computed from the cross-entropy loss (CE-loss). The inner loop ends when random noise converges to a batch of synthesized images. Then in the **Outer Loop**, we infer the predictions of the synthesized images using the pre-trained model and use these predictions as the soft labels for synthesizing the next batch of images. See section 3 for details.

more diverse and can better capture semantic relationships that exist in the original training data. In order to further improve the diversity, we propose a novel regional gradient updating scheme on synthesized images to match the random crop augmentation in training NAS.

We show that, the architecture accuracy rankings on the data synthesized with the proposed method produce more consistent correlation with the rankings on the original data. In turn, NAS on our synthesized data discovers the searched architecture with much higher accuracy. We demonstrate the feasibility of our data-free NAS conversion on three prevalent NAS algorithms: a reinforcement-learning-based algorithm (ProxylessNAS [4]), an evolution-based algorithm (Single Path One-Shot [8]) and a gradient-based algorithm (DARTS [15]).

We make four major contributions in this paper:

- We reveal, for the first time, that it is feasible to search architectures without relying on the original training data and propose a framework for data-free NAS.
- We identify properties of synthesized images that NAS requires, and propose a data synthesis method that uses recursive label calibration and regional update to generate images with sufficiently high diversity from the information stored in a pre-trained model for effective NAS.
- We validate the generalization ability of data-free NAS by integrating it with three different NAS algorithms and demonstrating competitive results.
- We further extend the scope of our data synthesis method and demonstrate that it also outperforms prior approaches for the data-free pruning and knowledge transfer tasks.

2 Related Work

Generative adversarial networks (GAN) [2,33] can generate images with high fidelity, but still need real images as a reference while training the generator, which is not fully data-free. Recently, Chen et al. [5] and Xu et al. [28] proposed to use a generator to synthesize images from a pre-trained model and simultaneously train the student network. Further, Yin et al. [29] proposed to synthesize images from the pre-trained teacher network using regularization terms and Jensen-Shannon divergence loss. However, such method is a general design without explicitly considering the requirements for architecture search and also ignoring the crucial factors like the semantic diversity in the latent feature and image spaces. In this work, we propose recursive label calibration and regional update to generate more diverse and semantically meaningful images to fulfill the demand of neural architecture search.

Neural Architecture Search (NAS) is a tool for automatic discovery of optimized neural network architectures under various practical constraints. To conduct NAS, it normally requires a search space, a search algorithm and a set of training data. Current NAS research mainly focuses on improving the search algorithms [20,34,1,35], designing the search space [21,7,30], reducing the search cost [3,11,19,4,15] and integrating direct metrics with the search process [27,8]. To our best knowledge, there is no previous literature directly studying the problem of data-free NAS. Thus, our work has many practical and useful guidelines on this problem for future research. One prior work [13] may be the closest one to ours, it proposed to conduct NAS without human-annotated labels. In our study, we take one step further and attempt to answer the question of whether NAS can be conducted even without the original data at all.

3 Our Method

In data-free neural architecture search, as we have no access to the original data $\mathbf{X} \in \mathbb{R}^{w \times h}$, we aim to use synthesized data $\hat{\mathbf{X}} \in \mathbb{R}^{w \times h}$ to search for the high-performing architecture \mathbf{A}^* in the search space of \mathcal{S} , with the NAS algorithm minimizing the loss:

$$\mathbf{A}^* = \operatorname{argmin}_{\mathbf{A} \in \mathcal{S}} \mathcal{L}(\mathbf{A}|\hat{\mathbf{X}}). \quad (1)$$

In this way, we target at finding an architecture that achieves high performance when evaluated on the target data \mathcal{X} :

$$\mathbf{A}^* \approx \operatorname{argmax}_{\mathbf{A} \in \mathcal{S}} \operatorname{Acc}_{\text{eval}}(\mathbf{A}|\mathbf{X}). \quad (2)$$

This requires the synthesized images to be semantically meaningful, diverse, and have a minimum domain gap with target data (*i.e.*, $\hat{\mathbf{X}} \sim \mathbf{X}$) to ensure that the architecture rankings on the synthesized images align well with the rankings on original data. Such that we can conduct data-free NAS by integrating the synthesized data and their corresponding soft labels with existing NAS algorithms.

3.1 Data Synthesis

We optimize the classification (cross-entropy) loss between the pre-trained model’s prediction $\mathbf{M}_{\text{pretrained}}(\hat{\mathbf{X}})$ on the synthesized data and the target label \mathbf{y} :

$$\min_{\hat{\mathbf{X}}} \mathcal{L}_{CE}(\mathbf{M}_{\text{pretrained}}(\hat{\mathbf{X}}), \mathbf{y}), \quad (3)$$

where \mathcal{L}_{CE} denotes the classification loss (*i.e.*, cross-entropy loss) and $\hat{\mathbf{X}}$ denotes input “image”.

Specifically, since one-hot label \mathbf{y} is unable to capture the underlying class relationship, we propose recursive label calibration to automatically learn the semantically-related soft labels $\hat{\mathbf{y}}$ and use $\hat{\mathbf{y}}$ for image synthesis. Furthermore, we propose a novel regional update scheme to improve the diversity of generated images.

Regularization (i) *Input-level Regularization:*

As a natural image taken from a real scene is unlikely to sharply vary in value between adjacent pixels, following [17], we impose a regularization term \mathcal{L}_{input} to penalize the overall variance in the synthesized data:

$$\mathcal{L}_{input} = \sum_{i,j} ((\hat{\mathbf{X}}_{(i+1,j)} - \hat{\mathbf{X}}_{(i,j)})^2 + (\hat{\mathbf{X}}_{(i,j+1)} - \hat{\mathbf{X}}_{(i,j)})^2) \quad (4)$$

where i, j denotes the index of each pixel in the image.

(ii) *Feature-level Regularization:*

Further, we impose a regularization term to align the high-level feature map statistics with the target images by enforcing the synthesized images to produce similar statistics in the feature maps as statistics calculated and stored in each BN layer of the pre-trained model, as [29].

$$\mathcal{L}_{feat} = \sum_l (\|\mathbf{E}_l(\hat{\mathbf{X}}) - \mathbf{E}_l(\mathbf{X})\|_2 + \|\mathbf{Var}_l(\hat{\mathbf{X}}) - \mathbf{Var}_l(\mathbf{X})\|_2) \quad (5)$$

Here, $\mathbf{E}_l(\hat{\mathbf{X}})$ and $\mathbf{Var}_l(\hat{\mathbf{X}})$ denote the mean and variance of the feature map of synthesized images in the l^{th} convolutional layer, $\mathbf{E}_l(\mathbf{X})$ and $\mathbf{Var}_l(\mathbf{X})$ denote the historical mean and variance of target images, which are stored in Batch-Norm [10] of the pre-trained model.

Recursive Label Calibration Importantly, we observe that the pre-trained model’s prediction on a natural image will spread as a distribution of logits, with the maximum value being the target class and other several peaks landing at similar classes, shown in Fig. 2 (a).

Thus, for encouraging synthesized images to model higher-level class correlation and to capture more subtle semantic information, we want the targets of synthesized images to be a distribution of semantically-related classes. Considering no original images are available, we cannot obtain the relationship between




Fig. 2. The pre-trained model’s prediction on the input image. (a) Natural image in the category “coffee mug”. Its prediction contains a peak at “coffee mug” and another peak value in the related class “cup”. (b) The image synthesized *w.r.t.* the “coffee mug” class as a one-hot hard label. The pre-trained model only strongly predicts this image as “coffee mug”. Meanwhile, there is a pattern on the surface of the mug that resembles coffee. (c) The image synthesized using recursive label calibration. It automatically identifies “cup” as a related class for the image synthesized *w.r.t.* the “coffee mug” category. The image looks more natural as well.

classes directly. However, we make an important observation that the pre-trained model’s prediction on the image synthesized with respect to the hard label also has fractional logits spread between semantically similar classes. But these logits are too weak to be reflected in the synthetic images. Thus, we propose recursive label calibration to amplify this distribution, which utilizes the soft prediction of the previously synthesized image as the new targets,

$$\hat{\mathbf{y}}_{t-1} = \mathbf{M}_{\text{pretrained}}(\hat{\mathbf{X}}_{t-1}), \quad (6)$$

replacing the hard label y in Eq. 3 to guide the image synthesizing process:

$$\hat{\mathbf{X}}_t^* = \min_{\mathbf{X}} \mathcal{L}_{CE}(\mathbf{M}_{\text{pretrained}}(\hat{\mathbf{X}}_t), \hat{\mathbf{y}}_{t-1}) \quad (7)$$

as also illustrated in Fig. 3.

After visualizing the images synthesized with recursive label calibration, we confirm that these images do learn the semantic relationships among classes. As shown in Fig. 2 (b), the image synthesized without label calibration is over-confident at the prediction of the “coffee mug” class. While in Fig. 2 (c), the prediction of the image synthesized with recursive label calibration automatically learns that “coffee mug” and “cup” are two related classes. Recursive label calibration encourages the synthesized images to learn class relationships as natural images instead of over-fitting to a single class, which in turn allows the synthesized images to encode more semantic information.




Fig. 3. An illustration of the proposed regional update scheme and recursive label calibration for image synthesis. In every iteration of the generation process, a 224×224 region is randomly cropped from the 256×256 input and we update the selected region using gradients calculated *w.r.t.* Eq. 3. After an image is synthesized, we use the pre-trained model’s prediction on the synthesized image as the soft label for computing the cross-entropy loss with the output logits of the next image batch.

In addition, the prediction of the most related classes differs between synthetic image batches due to stochasticity in the synthesis process. Since each synthesis target is now a weighted combination of related classes rather than a single class, the number of distinct targets is greatly increased. More targets lead to more diversity in the images synthesized from these targets and produce a synthesized dataset that better resembles the natural training set. We show that higher similarity between synthetic and natural dataset leads to consistency in evaluation accuracy between architectures trained on original data and the synthetic data.

Regional Update Scheme To further enhance synthesized image diversity, we propose a regional update scheme for synthesis process. The regional update is formulated as:

$$\mathbf{G}_{\hat{\mathbf{X}}} = \nabla_{\hat{\mathbf{X}}} \mathcal{L}_{CE}(\mathbf{M}_{\text{pretrained}}(\hat{\mathbf{X}}_{w,h \in \mathbf{R}_{\text{selected}}}), \mathbf{y}), \quad (8)$$

Instead of generating the images with the size required for forward computation in the neural network, *e.g.*, 224×224 for ImageNet dataset, we enlarge the size of the input tensor $\hat{\mathbf{X}}$, *e.g.*, 256×256 for ImageNet dataset. In every iteration, we randomly select a sub-region $\mathbf{R}_{\text{selected}}$, *e.g.*, 224×224 as the input to the pre-trained model and calculate the gradients $\mathbf{G}_{\hat{\mathbf{X}}}$. We only update the selected region, leaving the pixels outside of that region unchanged, as also shown in Fig. 3. This proposed regional update during image synthesis reflects the random crop data augmentation during training, which greatly increases the amount of trainable data and enhances the image diversity. Additionally, it can encourage the translation-invariance in the synthesized images.




Fig. 4. The proposed data-free neural architecture search framework using the synthesized images. We replace the original ones with the synthesized images and use the soft labels to compute the KL-divergence loss with the output logits of NAS.

3.2 Architecture Search

After extracting the classification-relevant information from the pre-trained model by constructing a synthetic dataset, we use that dataset to conduct neural architecture search. Fig. 4 illustrates the proposed data-free neural architecture search framework: data-free NAS can be applied to an existing NAS algorithm by replacing the natural training data with synthetic data, and the classification labels with soft labels from pre-trained model. We instantiate data-free NAS with three prevalent NAS algorithms: ProxylessNAS [4], DARTS [15] and SPOS [8], which are reinforcement-learning-based, gradient-based and evolution-based respectively:

The gradient-based neural architecture search jointly learn the architecture parameter α and the SuperNet weights \mathbf{W} , aiming to find α^* that minimizes the validation loss \mathcal{L}_{val} , with weights \mathbf{W}^* in the SuperNet obtained by minimizing the training loss \mathcal{L}_{train} [15].

$$\min_{\alpha} \mathcal{L}_{val}(\mathbf{W}^*(\alpha), \alpha) \quad (9)$$

$$\text{s.t. } \mathbf{W}^*(\alpha) = \underset{\mathbf{W}}{\operatorname{argmin}} \mathcal{L}_{train}(\mathbf{W}, \alpha) \quad (10)$$

The reinforcement-learning-based method use the policy gradient to update the architecture parameters \mathbf{g} to maximize the reward R [4].

$$\mathcal{L}(\alpha) = \mathbb{E}_{\mathbf{g} \sim \alpha} [R(\mathbf{A}_{\mathbf{g}})], \quad (11)$$

$$\nabla_{\alpha} \mathcal{L}(\alpha) = \mathbb{E}_{\mathbf{g} \sim \alpha} [R(\mathbf{A}_{\mathbf{g}}) \nabla_{\alpha} \log(\mathbf{p}(\mathbf{g}))], \quad (12)$$

where \mathbf{g} denotes the binary gates of choosing certain masks with probability \mathbf{p} .

The evolution-based search in SPOS disentangled SuperNet training and architectural parameter optimization. Specifically for SuperNet training:

$$\mathbf{W}^*(\boldsymbol{\alpha}) = \underset{\mathbf{W}}{\operatorname{argmin}}, \mathbb{E}_{\boldsymbol{\alpha} \sim \Gamma(\mathbf{A})} \mathcal{L}_{train}(\mathbf{W}, \boldsymbol{\alpha}), \quad (13)$$

where \mathbf{W} denotes the SuperNet weights, $\boldsymbol{\alpha}$ denotes the architecture parameters and $\Gamma(\mathbf{A})$ is the probability distribution of architecture sampling. After the supernet is trained, the weights can be used for evolutionary search in the second separate step.

In the search phase, data-free NAS explores the pre-defined search space using the same search algorithm as the NAS algorithm it integrates. Instead of using the original data for ranking different architectures, we show that data-free NAS can reliably estimate the ranking with synthetic data generated with the proposed method. Further, we show that these architectural rankings are consistent with rankings on the original data, meaning that data-free NAS algorithms can discover architectures that achieve high accuracy when evaluated on the target data.

4 Experiments

To verify the effectiveness of our proposed data synthesis method for NAS, we first conduct consistency experiments, showing that with the proposed data synthesis method, the synthesized dataset possesses high correlation with the original data. Then, with these synthetic data, we demonstrate the feasibility of data-free NAS in discovering the architectures that perform competitively when evaluated on the target data. Further, we show that our synthesized data is also helpful in enhancing the accuracy of other tasks like data-free pruning and knowledge transfer and outperforms previous works. Lastly, we visualize the synthetic data in Sec. *Visualization*, and find that the proposed recursive label calibration and regional update scheme can largely improve the semantic diversity of the synthetic data and helps capture the underlying class relationships.

4.1 Consistency Exploration

We conduct the consistency experiments on two search spaces: the DARTS search space [15], and the Single Path One-Shot (SPOS) search space [8]. The term *consistency* refers to the accuracy correlation between the architectures trained on the synthetic data and the original data.

DARTS Search Space on CIFAR-10 Dataset For DARTS search space, we randomly sample 100 architectures, and train each architecture from scratch using original CIFAR-10 data, synthetic data, or random noise separately and




Fig. 5. Correlation between the accuracy of the architectures sampled from the DARTS [15] search space on the original CIFAR-10 data and different sources of synthetic data (including random noise). Here, ρ denotes Spearman’s rank correlation.




Fig. 6. Accuracy correlation on the SPOS [8] search space between original ImageNet *vs.* random noise as well as data synthesized with different methods. ρ denotes Spearman’s rank correlation.

report the architecture’s accuracy when evaluated on original CIFAR-10 validation dataset. Fig. 5 shows the correlation between the accuracy of architectures trained on synthetic data and the original data. Spearman’s Rank Correlation [25], denoted as “ ρ ”, is calculated in order to quantify the correlations between accuracy on synthesized and original data. From Fig. 5 (a) we can see that the overall accuracy of the network trained on the random noise is lower than 50% and the ranking is highly noisy, the random noise can hardly guide NAS for finding a high-quality architecture. In contrast, synthesized data improves the correlation compared to random noise and recursive label calibration further enhances the correlation. This correlation supports our belief that a NAS algorithm applied on the good synthetic data is likely to discover architectures that perform well on the original data.

SPOS Search Space on ImageNet dataset We use the SPOS [8] search space to explore the more challenging task of architecture search on the large-scale ImageNet dataset. We randomly sample 1000 architectures from the SPOS search space, then evaluate their accuracy. As shown in Fig. 6 (a), for the large-scale ImageNet, simply using the random noise results in a totally uncorrelated accuracy between original and the “noise data”, the images synthesized with the regularization term produce an improved correlation compared to random noise, which, however, is still not sufficient for performing architecture search, as shown in Fig. 6 (b). The proposed recursive label calibration and regional update scheme further improve the correlation with ρ increasing from 0.87 to 0.96, in Fig. 6 (d), showing that the images synthesized with the proposed method

Table 1. Comparison between data-free DARTS and other NAS algorithms on CIFAR-10. † denotes using cutout.

Methods	Top-1 Err (%)	Params (M)	Data for NAS
NASNet-A [†] [35]	2.65	3.3	CIFAR-10
BlockQNN [32]	3.54	39.8	CIFAR-10
AmoebaNet-A [†] [20]	3.12	3.1	CIFAR-10
PNAS [14]	3.41 ± 0.09	3.2	CIFAR-10
ENAS [†] [19]	2.89	4.6	CIFAR-10
Random search [†] [15]	3.29 ± 0.15	3.2	CIFAR-10
DARTS [†] [15]	2.76 ± 0.09	3.3	CIFAR-10
Data-free DARTS	2.68 ± 0.09	3.3	Synthesized data

Table 2. Generalization of architecture searched with data-free DARTS [15] from CIFAR-10 to ImageNet.

Methods	Top-1 Err (%)	Params (M)	Data for NAS
DARTS [15]	26.7	4.7	ImageNet
Data-free DARTS	26.4	4.7	Synthesized data

produce a more correlated architecture ranking, which better guarantees the architecture searched on the synthesized dataset will achieve high accuracy on the target dataset.

4.2 Search Results

We investigate the effectiveness and generality of our data-free neural architecture search framework by testing it with three prevalent neural architecture search algorithms: DARTS [15], SPOS [8] and ProxylessNAS [4].

Implementation Details

Our experiments on DARTS are targeted at classification over CIFAR-10 [12] dataset and our experiments on SPOS and ProxylessNAS are targeted at classification over ImageNet [22] dataset. More experimental details can be referred to our Appendix.

Instantiations

Data-free DARTS: The architecture found by using DARTS with the data synthesized with the proposed method achieves 2.68% test error. As shown in Table 1, this is comparable to the architecture found when using DARTS with the original CIFAR-10 data. The search result of using data synthesized without label calibration is comparable to random search. This shows that the proposed synthesis method generates data with high correlation to the original CIFAR-10 data, which provides a basis for searching architectures on synthetic data that achieve high performance when evaluated on the original data. Further, the architecture discovered from the data synthesized with label calibration also

Table 3. Comparison between data-free SPOS, original SPOS [8] as well as other baseline results. “All choice” refers to the baseline algorithm where the same operation is chosen for all layers. “All Choice _3, _5, _7” denotes choosing only a ShuffleNet [31] block with 3×3 , 5×5 , or 7×7 convolution, respectively. “Choice _x” denotes using the Xception block [6].

Methods	Top-1 Err (%)	FLOPs (M)	Data for NAS
all choice _3	26.6	324	ImageNet
all choice _5	26.5	321	ImageNet
all choice _7	26.4	327	ImageNet
all choice _x	26.5	326	ImageNet
Random Select	~ 26.3	~ 320	ImageNet
Random Search	26.2	323	ImageNet
SPOS [8]	25.7	319	ImageNet
Data-free SPOS	25.8	316	Synthesized data

Table 4. Comparison between RL-based ProxylessNAS integrated with our data-free NAS framework and the original ProxylessNAS. We choose the targeting metrics as FLOPs.

Methods	Top-1 Err (%)	FLOPs(M)	Data for NAS
ProxylessNAS [4]	24.4	467	ImageNet
Data-free ProxylessNAS	24.2	465	Synthesized data

generalizes well to the ImageNet dataset and achieves slightly higher accuracy than original DARTS, shown in Table 2.

Data-free Single Path One-Shot: As shown in Table 3, compared to data synthesized without label calibration, the data synthesized with label calibration provides better guidance and results in higher final accuracy. The architecture discovered using synthesized data with label calibration achieves 74.2% top-1 accuracy. This accuracy is comparable to the results obtained by the SPOS search on the original ImageNet. This result also far exceeds random search as well as the baseline method of choosing the same operation for all layers, demonstrating the feasibility of using synthetic images for data-free NAS on a large-scale dataset.

Data-free ProxylessNAS: We adopt the RL-based ProxylessNAS targeting at the FLOPs constraint. Table 4 shows that ProxylessNAS, when integrated with our data-free framework, also achieves accuracy comparable to ProxylessNAS searching on the original data.

4.3 Extension Tasks

Data-free Pruning: We show that the proposed data-free NAS can be applied to pruning tasks via integrating with a search-based pruning method, MetaPrun-

Table 5. Comparison for data-free pruning on ResNet-50 structure.

Methods	Data Type	Top-1 Err (%)	FLOPs (G)
ImageNet	Original	23.4	4.1
BigGAN [2]	GAN synthesized	37.0	~1.2
DI [29]	Synthesized	44.1	~1.2
ADI [29]	Synthesized	39.3	~1.2
Ours	Synthesized	36.5	1.0

Table 6. The top-1 error of data-free knowledge transfer using ResNet-34 as the pre-trained teacher model for synthesize images and train a ResNet-18 student model from scratch for CIFAR-10.

Methods	Noise	DeepDream [17]	DAFL [5]	ADI [29]	Ours
Top-1 Err (%)	86.39	70.02	7.78	6.74	5.97

ing [16]. We use synthesized ImageNet images to guide MetaPruning for finding the best pruning ratio in each layer and train the searched pruned network from scratch also with the synthesized images. Results in Table 5 show that our data-free pruning achieves much higher accuracy than the previous state-of-the-art data-free pruning [29]. It further surpasses pruning using GAN-synthesized images. See the appendix for full training details.


Data-free Knowledge Transfer: The synthesized images can also serve as a foundation for knowledge transfer from a pre-trained teacher to the student network through training the student network from scratch with knowledge distillation [9,24,18,23] on the synthesized images. Compared to the previous state-of-the-art data-free learning methods [29,5], we achieve higher knowledge transfer accuracy when the target dataset is CIFAR-10 or ImageNet, as shown in Table 6 and 7. Full training details are included in the appendix.

4.4 Visualization

In Fig. 7, we can observe that images synthesized with regularization terms only have homogeneous color palettes and similar backgrounds, but when using the proposed label calibration and regional update scheme for synthesis, the images exhibit more diverse feature and look more realistic. Fig. 8 further shows a promising finding that the images synthesized with recursive label calibration do capture the underlining class relationships in a similar manner to the natural images. These attributes produce a good accuracy correlation between architectures trained on synthesized images and natural images which in turn contributes to the success of data-free NAS.

Table 7. Data-free knowledge transfer on ImageNet from pre-trained ResNet-50 to the same network initialized from scratch.

Methods	Data Type	Data Amount	Epochs	Top-1 Err (%)
ImageNet	Original	1.3M	250	23.4
BigGAN [2]	GAN synthesized	215K	90	36.0
ADI [29]	Synthesized	140K	250	26.2
Ours	Synthesized	140K	250	25.9
Ours	Synthesized	140K	500	24.8

**Fig. 7.** Synthesized 256×256 images with ResNet-50 optimized on ImageNet as the pre-trained network. We visualize three classes (“bulbul”, “schooner” and “seashore”) with different data synthesis methods.**Fig. 8.** Recursive label calibration automatically learns semantically-related labels for the synthetic images.

5 Conclusion

We have presented a novel framework that can conduct neural architecture search (NAS) without access to the original data. In order to perform data-free NAS, we developed a new recursive label calibration method and regional update strategy which automatically discover and encode the relationships between classes in soft labels and generate images *w.r.t.* these soft labels, while preserving the diversity of generated images. We demonstrate the effectiveness of our proposed method with three typical NAS algorithms. Our experimental results show that using the recovered data from a pre-trained model, NAS algorithms using our data synthesis method can obtain performance comparable to NAS algorithms using the original training data. This verifies that it is feasible to conduct NAS without original data if the synthesis method is well designed. In addition, we demonstrate that our synthetic data can produce state-of-the-art results for data-free pruning as well as knowledge transfer.

References

1. Baker, B., Gupta, O., Naik, N., Raskar, R.: Designing neural network architectures using reinforcement learning. arXiv preprint arXiv:1611.02167 (2016) [1](#), [4](#)
2. Brock, A., Donahue, J., Simonyan, K., et al.: Large scale gan training for high fidelity natural image synthesis. arXiv preprint arXiv:1809.11096 (2018) [4](#), [13](#), [14](#)
3. Brock, A., Lim, T., Ritchie, J.M., Weston, N.: Smash: one-shot model architecture search through hypernetworks. arXiv preprint arXiv:1708.05344 (2017) [4](#)
4. Cai, H., Zhu, L., Han, S., et al.: Proxylessnas: Direct neural architecture search on target task and hardware. arXiv preprint arXiv:1812.00332 (2018) [1](#), [3](#), [4](#), [8](#), [11](#), [12](#)
5. Chen, H., Wang, Y., Xu, C., Yang, Z., Liu, C., Shi, B., Xu, C., Xu, C., Tian, Q.: Data-free learning of student networks. In: Proceedings of the IEEE International Conference on Computer Vision. pp. 3514–3522 (2019) [4](#), [13](#)
6. Chollet, F.: Xception: Deep learning with depthwise separable convolutions. In: Proceedings of the IEEE conference on CVPR. pp. 1251–1258 (2017) [12](#)
7. Dai, X., Zhang, P., Wu, B., Yin, H., Sun, F., Wang, Y., Dukhan, M., Hu, Y., Wu, Y., Jia, Y., et al.: Chamnet: Towards efficient network design through platform-aware model adaptation. arXiv preprint arXiv:1812.08934 (2018) [4](#)
8. Guo, Z., Zhang, X., Mu, H., Heng, W., Liu, Z., Wei, Y., Sun, J.: Single path one-shot neural architecture search with uniform sampling. arXiv preprint arXiv:1904.00420 (2019) [3](#), [4](#), [8](#), [9](#), [10](#), [11](#), [12](#)
9. Hinton, G., Vinyals, O., Dean, J.: Distilling the knowledge in a neural network. arXiv preprint arXiv:1503.02531 (2015) [13](#)
10. Ioffe, S., Szegedy, C.: Batch normalization: Accelerating deep network training by reducing internal covariate shift. arXiv preprint arXiv:1502.03167 (2015) [5](#)
11. Jin, H., Song, Q., Hu, X.: Efficient neural architecture search with network morphism. arXiv preprint arXiv:1806.10282 (2018) [1](#), [4](#)
12. Krizhevsky, A., Hinton, G.: Learning multiple layers of features from tiny images. Tech. rep., Citeseer (2009) [11](#)
13. Liu, C., Dollár, P., He, K., Girshick, R., Yuille, A., Xie, S.: Are labels necessary for neural architecture search? arXiv preprint arXiv:2003.12056 (2020) [4](#)
14. Liu, C., Zoph, B., Neumann, M., Shlens, J., Hua, W., Li, L.J., Fei-Fei, L., Yuille, A., Huang, J., Murphy, K.: Progressive neural architecture search. In: Proceedings of the European Conference on Computer Vision (ECCV). pp. 19–34 (2018) [1](#), [11](#)
15. Liu, H., Simonyan, K., Yang, Y., et al.: Darts: Differentiable architecture search. In: International Conference on Learning Representations (2019) [1](#), [3](#), [4](#), [8](#), [9](#), [10](#), [11](#)
16. Liu, Z., Mu, H., Zhang, X., Guo, Z., Yang, X., Cheng, K.T., Sun, J.: Metapruning: Meta learning for automatic neural network channel pruning. In: Proceedings of ICCV. pp. 3296–3305 (2019) [13](#)
17. Mordvintsev, A., Olah, et al., C., Tyka, M.: Inceptionism: Going deeper into neural networks (2015) [5](#), [13](#)
18. Müller, R., Kornblith, S., Hinton, G.: When does label smoothing help? In: NeurIPS (2019) [13](#)
19. Pham, H., Guan, M.Y., Zoph, B., Le, Q.V., Dean, J.: Efficient neural architecture search via parameter sharing. arXiv preprint arXiv:1802.03268 (2018) [4](#), [11](#)
20. Real, E., Aggarwal, A., Huang, Y., Le, Q.V.: Regularized evolution for image classifier architecture search. arXiv preprint arXiv:1802.01548 (2018) [1](#), [4](#), [11](#)

21. Real, E., Moore, S., Selle, A., Saxena, S., Suematsu, Y.L., Tan, J., Le, Q.V., Kurakin, A.: Large-scale evolution of image classifiers. In: Proceedings of the 34th International Conference on Machine Learning-Volume 70. pp. 2902–2911. JMLR.org (2017) [1](#), [4](#)
22. Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., Huang, Z., Karpathy, A., Khosla, A., Bernstein, M., et al.: Imagenet large scale visual recognition challenge. *International Journal of Computer Vision* **115**(3), 211–252 (2015) [11](#)
23. Shen, Z., He, Z., Xue, X.: Meal: Multi-model ensemble via adversarial learning. In: Proceedings of the AAAI Conference on Artificial Intelligence. vol. 33, pp. 4886–4893 (2019) [13](#)
24. Shen, Z., Liu, Z., Xu, D., Chen, Z., Cheng, K.T., Savvides, M.: Is label smoothing truly incompatible with knowledge distillation: An empirical study. In: International Conference on Learning Representations (2021) [13](#)
25. Spearman, C.: The proof and measurement of association between two things. (1961) [10](#)
26. Tan, M., Chen, B., Pang, R., Vasudevan, V., Le, Q.V.: Mnasnet: Platform-aware neural architecture search for mobile. arXiv preprint arXiv:1807.11626 (2018) [1](#)
27. Wu, B., Dai, X., Zhang, P., Wang, Y., Sun, F., Wu, Y., Tian, Y., Vajda, P., Jia, Y., Keutzer, K.: Fbnet: Hardware-aware efficient convnet design via differentiable neural architecture search. arXiv preprint arXiv:1812.03443 (2018) [1](#), [4](#)
28. Xu, S., Li, H., Zhuang, B., Liu, J., Cao, J., Liang, C., Tan, M.: Generative low-bitwidth data free quantization. arXiv preprint arXiv:2003.03603 (2020) [4](#)
29. Yin, H., Molchanov, P., Alvarez, J.M., Li, Z., Mallya, A., Hoiem, D., Jha, N.K., Kautz, J.: Dreaming to distill: Data-free knowledge transfer via deepinversion. In: Proceedings of the CVPR. pp. 8715–8724 (2020) [4](#), [5](#), [13](#), [14](#)
30. Ying, C., Klein, A., Christiansen, E., Real, E., Murphy, K., Hutter, F.: Nas-bench-101: Towards reproducible neural architecture search. In: International Conference on Machine Learning. pp. 7105–7114 (2019) [1](#), [4](#)
31. Zhang, X., Zhou, X., Lin, M., Sun, J.: Shufflenet: An extremely efficient convolutional neural network for mobile devices. In: Proceedings of the IEEE conference on computer vision and pattern recognition. pp. 6848–6856 (2018) [12](#)
32. Zhong, Z., Yang, Z., Deng, B., Yan, J., Wu, W., Shao, J., Liu, C.L.: Block-qnn: Efficient block-wise neural network architecture generation. arXiv preprint arXiv:1808.05584 (2018) [11](#)
33. Zhu, J.Y., Park, T., Isola, P., Efros, A.A.: Unpaired image-to-image translation using cycle-consistent adversarial networks. In: Proceedings of the IEEE international conference on computer vision. pp. 2223–2232 (2017) [4](#)
34. Zoph, B., Le, Q.V.: Neural architecture search with reinforcement learning. arXiv preprint arXiv:1611.01578 (2016) [4](#)
35. Zoph, B., Vasudevan, V., Shlens, J., Le, Q.V.: Learning transferable architectures for scalable image recognition. In: Proceedings of the IEEE conference on computer vision and pattern recognition. pp. 8697–8710 (2018) [1](#), [4](#), [11](#)