

Fig. 4: Low-dimensional representation of images. Each point represents one image. CLIP embeddings were extracted for all images and then projected to a 2D space using the UMAP algorithm. HaloQuest real images occupy a similar semantic distribution to VQA v2 images, while the synthetic images are entirely novel.

A Discussion and Future Work

This section explores the impact of this work and its potential to shape future research directions in the field, including discussion on the semantic novelty of synthetic images, solving hallucination comprehensively, multimodal hallucination, finding nuance in responses with Auto-Eval, and broader societal impacts.

A.1 Visualizing Semantic Novelty in Synthetic Images

Beyond cost-effectiveness and scalability, HaloQuest leverages prompt-based synthetic images to access a wider spectrum of visual scenarios, including unusual, complex, and abstract scenes, which are challenging or infeasible to obtain from real-world sources. This is particularly critical given the growing prevalence of synthetic images in real-world applications, necessitating the development of models resistant to hallucinations. Figure 4 illustrates this distinction by demonstrating the semantic dissimilarity between synthetic and real images, including those from the VQA v2 [15] dataset, within the embedding space. This finding underscores the importance and unique contribution of the synthetic images in HaloQuest.

A.2 Hallucination Remains an Unsolved Problem

Experiments using HaloQuest highlight the severity of hallucination in current models. While fine-tuning on HaloQuest demonstrates significant reduction in hallucination rates, the problem persists. This aligns with trends in related work, where techniques can identify and alleviate hallucination but fall short of a complete solution. Tackling hallucination comprehensively will likely require a multi-pronged approach. Further exploration into integrating symbolic reasoning, scaling both model parameters and dataset size, and potentially even rethinking model architectures might hold the key. This work represents an important step, but underscores that the quest to eliminate hallucination in VLMs will require continued innovation and research.

A.3 Multimodal Hallucination

This paper focuses on visual hallucination in VLMs, a phenomenon related to but distinct from text-only hallucination in LLMs. As AI systems continue to operate within multimodal environments (code, video, audio, etc.), the necessity of addressing hallucination across these varied modalities will become increasingly important. The key question remains: are there techniques that are capable of reducing hallucination universally, or will modality-specific approaches be essential? Exploiting inherent structural differences between modalities might reveal new insights, but developing techniques that are modality-agnostic may be a more efficient path forward. The development of datasets like HaloQuest serves as a good starting point, emphasizing the importance of designing challenging benchmarks as the field looks towards tackling hallucination in the broader landscape of multimodal AI.

A.4 Unconvering Nuance with Auto-Eval

This paper uses human evaluation as the gold standard for measuring model performance, but also contributes a novel Auto-Eval mechanism that holds promise for efficient evaluation at scale in future work. Human evaluation is important for benchmarking the Auto-Eval system itself. Interestingly, the relationship is reciprocal: exploring instances where human and Auto-Eval judgments diverge was useful for finding nuanced and challenging cases that highlight the subtle nature of hallucination detection. In a limited number of scenarios, this analysis even led to refinements in the ground truth labels. This demonstrates the potential of human and automated evaluation systems to work in tandem, driving continuous improvement in detecting and understanding hallucination.

A.5 Societal Impact

While this work primarily centers on the creation of a novel dataset, the potential societal impacts are significant. HaloQuest aims to provide a crucial tool for mitigating hallucination in VLMs, thereby improving their robustness and

reducing the likelihood of erroneous or misleading outputs. This has implications for real-world applications where safety and reliability are paramount, such as autonomous systems or medical image analysis. However, it is important to acknowledge that like any technology, datasets can be used for both beneficial and potentially harmful purposes. Bad actors could leverage datasets like HaloQuest to intentionally train models to generate misleading or deceptive content tailored to exploit model weaknesses. This fact underscores the importance of ongoing research into the detection and mitigation of such malicious use of AI systems.

B Instructions for Crowdworkers Writing Questions

Crowdworkers were given the following instructions when asked to draft questions and answers for a given image:

> For each input image, please write 2 challenging questions as described below and also 3 answers for each question. In case it is hard to write a challenging question, skip the writing and write "skip".
>
> **First question**
>
> **The first question should ask something about a visual element related to the image which is not possible to answer by looking at the image.** (We've discovered that AI models often struggle to express uncertainty and instead generate answers for these types of questions. Therefore, we wish to create a dataset specifically for evaluating AI models on these types of questions.) These are some example cases for writing these types of questions.
> - The question **asks some details about a visual element that is not visibly present in the image**, consequently, we either cannot answer the question, or the answer to the question implies that the subject is not present. Please provide questions about elements that, while not visible, are **relevant** to the scene depicted in the image. For instance, you could ask about something that is hidden or cropped in the current context. Alternatively, you might consider asking about a detail that would likely be found in a similar image. For example please see the first question about the cat image below.
> - The question **asks about specific information regarding one object which is visible in the image**. However it is not possible to know the answer by checking the image. For example the question asks about the name of a building, art, street, mountain, ect which is presented in the image. However, by checking the image it's impossible to answer. Because the image doesn't show a popular landmark/object and also the name is not visible in the image.
>
> **We want to create challenging questions about the input image. But in some cases it's hard to create challenging questions (for**

example the input image is too simple). In these cases please just write "skip" instead of writing a question.

Second question

The **second question should ask about a subtle detail presented in the image which we are able to easily provide a clear answer and the answer does not vary upon personal preferences or opinions**. Please concentrate on minor details within the image that would be challenging to answer. For instance, if the image features a cat, a question about the cat's color is straightforward. However, asking about the specific detail of the cat's paw positioning could be more challenging (see the cat image below). Please also keep in mind that we should be able to **clearly** answer the challenging question by checking the image.

We want to create challenging questions about the input image. But in some cases it's hard to create challenging questions (for example the input image is too simple). In these cases please just write "skip" instead of writing a question.

Answers

For each question, please also provide **three correct responses**. Please format your responses as follows: "Answer 1; Answer 2; Answer 3". Make sure to separate each answer with a semicolon (;) and a space. Please see example responses below.

C Auto-Eval Implementation Details

Table 4 of the main paper explored different implementations of Auto-Eval. Each of the three implementations of Auto-Eval are detailed below. The first implementation uses a simple text-only prompt (Figure 5). The second implementation adds a basic Langfun schema that the model must populate (Figure 6). The final implementation used throughout the paper also includes additional schema attributes that prompt the model to reason deeply about the main points of the response and ground truth before making a final decision (Figure 7). This reasoning is demonstrated in Figure 8. The result is an Auto-Eval system that has higher agreement with human raters than text-only prompting or the basic schema. All implementations use Gemini Pro as the underlying LLM.

D Finetuning Experiment Implementation

The results in Table 5 were obtained in the following way. For BLIP2, tuning focuses solely on the Q-Former's parameters to enhance question-answering capa-

```
def compute_prediction(inputs):
    _, question, prediction, groundtruth = inputs

    r = lf.query(prompt="""Your task is to determine if the model response is correct given the question and groundtruth response.
    Ensure to interpret the model response in accordance to the the question.

    If the question asks about a detail of an element that is not present in the image, A prediction of "yes", "no" or "nothing"
        should be considered incorrect because it inaccurately suggests that the element is presented in the image.
    The correct prediction in such cases should acknowledge the absence of the element in question by stating the element is not
        present.

    If prediction says that it can not assist or cannot provide an answer, then the prediction is incorrect.
    If the question is about counting, then the prediction is correct only it matches the groundtruth counts exactly.

    question={{question}},

    groundtruth={{groundtruth}},

    prediction={{prediction}}

    Is the prediction correct?
    Respond with True or False without any extra information.
    """,
    question=question,
    groundtruth=groundtruth,
    prediction=prediction,
    lm=gemini_pro)
    return r
```

Fig. 5: Text-only prompting

```
class PredictionEvaluation(pg.Object):
  question: str
  model_response: str
  groundtruth_response: str
  is_prediction_correct: bool

def compute_prediction(inputs):
    _, question, model_response, groundtruth_response = inputs

    r = lf.query(prompt="""Your task is to determine if the model response is correct given the question and groundtruth response.
    Ensure to interpret the model response in accordance to the the question.

    If the question asks about a detail of an element that is not present in the image, A prediction of "yes", "no" or "nothing"
        should be considered incorrect because it inaccurately suggests that the element is presented in the image.
    The correct prediction in such cases should acknowledge the absence of the element in question by stating the element is not
        present.

    If prediction says that it can not assist or cannot provide an answer, then the prediction is incorrect.
    If the question is about counting, then the prediction is correct only it matches the groundtruth counts exactly.

    question={{question}},
    model_response={{model_response}}
    groundtruth_response={{groundtruth_response}},

    """,
    schema=PredictionEvaluation,
    question=question,
    groundtruth_response=groundtruth_response,
    model_response=model_response,
    lm=gemini_pro)
    return r.is_prediction_correct
```

Fig. 6: Basic Langfun schema

```
class PredictionEvaluation(pg.Object):
  question: str
  model_response: str
  groundtruth_response: str
  sentence_interpret_model_response_main_point: str
  sentence_interpret_groundtruth_response_main_point: str
  is_prediction_correct: bool

def compute_prediction(inputs):
    _, question, model_response, groundtruth_response = inputs

    r = lf.query(prompt="""Your task is to determine if the model response is correct given the question and groundtruth response.
    Ensure to interpret the model response in accordance to the the question.

    If the question asks about a detail of an element that is not present in the image, A prediction of "yes", "no" or "nothing"
        should be considered incorrect because it inaccurately suggests that the element is presented in the image.
    The correct prediction in such cases should acknowledge the absence of the element in question by stating the element is not
        present.

    If prediction says that it can not assist or cannot provide an answer, then the prediction is incorrect.
    If the question is about counting, then the prediction is correct only it matches the groundtruth counts exactly.

    question={{question}},
    model_response={{model_response}}
    groundtruth_response={{groundtruth_response}},

    """,
    schema=PredictionEvaluation,
    question=question,
    groundtruth_response=groundtruth_response,
    model_response=model_response,
    lm=gemini_pro)
    return r.is_prediction_correct
```

Fig. 7: Advanced Langfun schema

```
PredictionEvaluation(
  question = 'What color is the lion in the photo?',
  model_response = "The image you've uploaded is an illustration, not a photograph, and it features giraffes and birds in a golden
      hour scene of what appears to be the African savanna. I do not see a lion in this particular image. The dominant colors are
      shades of yellow, orange, and black, creating a silhouette effect against the setting or rising sun. If there were a lion in
      the image, it would likely be depicted in a similar silhouette form.",
  groundtruth_response = 'There is no lion in the photo; There are no lions; There is no lion,',
  sentence_interpret_model_response_main_point = 'There is no lion in the image.',
  sentence_interpret_groundtruth_response_main_point = 'There is no lion in the image.',
  is_prediction_correct = True
)

PredictionEvaluation(
  question = 'Is the bee perched on the petals of the flower?',
  model_response = 'yes',
  groundtruth_response = 'There is no bee in the image.; There is no bee perched on the petals of the flower.; The image does not
      include a bee.',
  sentence_interpret_model_response_main_point = 'The bee is perched on the petals of the flower.',
  sentence_interpret_groundtruth_response_main_point = 'There is no bee in the image.',
  is_prediction_correct = False
)
```

Fig. 8: Example Auto-Eval outputs. The first example demonstrates how Auto-Eval identifies the main point in the model response and ground truth to be the absence of a lion in the image, which in turn leads to judging the response as correct. The second example shows conflicting main points, and so the response is accurately judged as being incorrect.

bilities, while the image encoder and LLM remain unchanged [22,62]. MiniGPT4 employs a Vision Transformer for image encoding and Vicuna for text decoding, connected by a Q-Former [11,65]. Its tuning targets a learnable linear projection layer to align visual features with Vicuna's embeddings, improving visual-textual integration. In mPLUG-Owl, the tuning strategy freezes the pre-trained visual encoder and abstractor, concentrating on improving the text decoder (Vicuna) through low-rank adaptation [56]. This enhances the model's ability to process and interpret visual-text data. A language generation loss is used to effectively minimize hallucination while maintaining generalizability.

To align our fine-tuning process with established best practices, we adhere to the methodologies outlined by [31,65] for crafting fine-tuning instructions. While both VQA v2 and HaloQuest fall within the domain of Visual Question Answering tasks, they differ significantly in their answer formats. VQA v2 adopts a "closed-book" approach, limiting responses to a predefined list of short answers that include both single words and phrases. Conversely, HaloQuest permits free-form answers, embracing a more flexible response format. This divergence necessitates the formulation of task-specific instructions to optimize model performance during fine-tuning.

For the VQA v2 task, the instruction template provided to BLIP2 is structured as follows:

```
<Image> Question: {Question} Short Answer:
```

This template is designed to elicit concise, predefined responses, aligning with VQA v2's structured answer requirements.

In contrast, for the HaloQuest task, we modify the instruction template to accommodate open-ended responses:

```
<Image> Question: {Question} Answer:
```

This adjustment signals the model to generate elaborated and unrestricted responses, catering to the open-ended nature of HaloQuest.

Similarly, for MiniGPT4 and mPLUG-Owl, we customize the prompts to align with the task requirements of VQA v2 and HaloQuest. These tailored prompts are designed to guide the models towards generating the expected form of answers, whether they be concise answers for VQA v2 or more elaborate responses for HaloQuest. Similarly, for the VQA v2 task, the instruction for MiniGPT4 and mPLUG-Owl is as follows:

```
<Image> Answer the question. Q: {Question}
```

Conversely, for the HaloQuest task, the prompt is adjusted to encourage responses in either words or phrases:

```
<Image> Answer the question in words or phrases. Q: {Question}
```

By tailoring the instructions to the specific needs of each task, we ensure that the fine-tuning process enhances the relevance and accuracy of the model's outputs, effectively addressing the unique objectives and constraints of VQA v2 and HaloQuest.